VALVE ACTUATOR - 24 V ON/OFF NO

# **Product description**

# A41405 – Valve actuator 24 V On/Off (NO)

A41405 has replaced A4104

# **Introduction A41405**

Valve actuator A41405 is intended for On/Off operation of valves. The actuator is mounted with the aid of valve adapter rings that enable problem-free installation of the various adjustment and mixing valves that are available on the market.

### **Function**

The 24 VAC On/Off signal is pulsed to a 0-4 mm movement (stroke length).

The valve actuator is equipped with function indication. A blue band around the projecting extension on the top shows how much the actuator is activated (closed).

Radiator valve A41405 is open when the power is off.



See the product description for adapter rings for a list of a selection of adapter rings for valves in normal use. VA32, VA54, VA78 and VA80 can normally be ordered from Lindinvent.

# **Technical specifications**

### General

Control signal 24 VAC On/Off

Actuator position with loss of power

Open (NO)

**Dimension** 

48 x 44 x 50.3+7 mm (LxWxH)

Weight

100 g

Material

Polyamide encapsulation

Colour

Gray (RAL 7035)

IP class

Encapsulation complies with IP54

Connection cable


1000 mm, 2x0,.5 mm<sup>2</sup>


Ambient temperature

Max 60°C



Valve actuator A41405 without adapter ring.





Installation height

## Electrical system

Supply voltage 24 VAC

Output (in operation)

1.0 W

Power consumption (when switching on)

Max 300 mA

## **Control**

**First-Open function** 

No

Closing/opening time

3.5 min

Stroke length

4 mm

Operative force

100 N

## **Product description**

# A41405 - Valve actuator 24 V On/Off (NO)

A41405 has replaced A4104

## **Additional product documentation A41405**

Table 1: Additional documentation for A41405 can be obtained via links on the product's website under Products at www.lindinvent.se

Document	Available	Not available	Comments
Installation Instruction			
Start-up instruction			Not applicable
Maintenance instruction			Regarded as maintenance-free
External connection diagram			
Environmental product declaration			Assessed by Byggvarubedömningen and Sundahus
User information			Not applicable
Modbus list			Not applicable
AMA text			

Product documentation can be downloaded via www.lindinvent.se/produkter/



#### Contact

www.lindinvent.se Tel: 046–15 85 50 Lindinvent – Smarter indoor climate. Greener buildings.

The company offers products and systems for controlling ventilation, lighting, solar shading and local utilization. Equipment and climate solutions are being developed for offices, schools, hospitals, laboratories and similar working environments. Lindinvent's systems work together to provide high indoor comfort and the lowest possible energy use.

